



RibBracket III

PV Kit 2.0


RibBracket III

(4x) 1/4" Diameter 1" Length
5/16" Hex Screw





0.40" x 1.25" Slotted Hole

Slot for Hex Flange Nut




(2x) Factory Applied EPDM

(4x) ϕ .31" Through Hole for Fasteners



Designed to fit popular North American and Indian Profiles such as PBR-Panel, R-Panel, Kirby Roof (KR), and other similarly dimensioned profiles.

Sample Rib Roof Panel



FOR STANDING SEAM SPECIFIC MECHANICAL LOAD TEST INFORMATION AND CLAMP INSTALLATION INFORMATION PLEASE VISIT: WWW.S-5.COM

MATERIAL: 6005A T61		METAL ROOF INNOVATIONS, LTD. 8655 TABLE BUTTE RD COLORADO SPRINGS, CO 80908 719-495-0518 719-495-0045(FAX)	
EST ASSEMBLY WEIGHT 0.180 lbs			
SUPPLIED HARDWARE: M8-1.25 Flange Nut (4x) 1/4"-1" Stainless Steel Self-Tapping Screw with 5/16" Hex Head	TITLE RibBracket III [CCD]		
SCALE: 1:2	DRAWING NO. PBR-A-0-A	DRAWN BY Jesse Winternitz	DATE 7/1/2019
WEIGHTS: Bracket: 0.0935 lbs Screw: 0.0180 lbs Nut: 0.0145 lbs	S-5!® PRODUCTS ARE PROTECTED BY MULTIPLE U.S. PATENTS INCLUDING 5,228,248, 5,983,588 AND 6,164,033 (OTHERS ISSUED AND PENDING). EUROPEAN PATENTS ARE ALSO APPLIED FOR AND PENDING UNDER THE PATENT COOPERATION TREATY WITH DIVISIONAL FILING RIGHTS RETAINED. METAL ROOF INNOVATIONS, LTD. (LICENSOR OF S-5!® TECHNOLOGY) AGGRESSIVELY PROSECUTES PATENT INFRINGEMENT.		